Chaingel





- •Very wide range of applications
- Strong adhesion
- •Unique penetrating effect
- Dust repellent
- •No corrosion on the surface

Applications

For lubrication of axles, gearwheels, roller bearings, conveyor belts, compressed air tools, chains, lifting equipment, locks, tools, transmissions, cables, connecting rods, open worm wheels, gland nuts, etc.

Processing

Remove any excess gel with Zettex Proficleaner

Packaging

• Aerosol 500 ml.

Colour

• Transparent/yellow

Safety recommendations

• Please refer to safety information leaflet

Technical data

Properties	Specification
Odour	paraffin
Phase transition point/ boiling point °C	approx. 60
Density g/ml (20°C	approx. 0.818 DIN 51757
Vapour pressure mbar (20°C	n.b.
Viscosity mPa (20°C	< 10 dynamic
pH value undiluted (20°C):	n.m. DIN 19261
pH value 1% solution (20°C)	n.m.
Autoignition temperature (20°C)	250 DIN 51794
Explosive limits Full % lower	n.b. DIN 51649
Full % upper	n.n. DIN 51649
Water solubility (20°C)	20 mg/l

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands T +31 (0)888-93 88 39 • F +31(0)888-93 88 88 I www.zettex.com • E info@zettex.com

Product description

Zettex Chaingel is a high quality universal lubricant and chain spray. Chaingel is resin and acid free, friendly to the skin, corrosion resistant and waterproof. It forms an active, permanent and flexible lubricant film. Sprays with the consistency of water and sets between the parts to be lubricated.

Material

Full Synthetic grease