



Product description

Zettex Easy Silicon N is an Oxym based neutral curing silicon for sealing windows, facades and all type of joints in the building industry. Zettex Easy Silicon N is fast drying and UV resistant.

Material

Neutral oxime silicone

Advantages

- Low modulus and high elasticity.
- High movement capability. Meets the requirements of ISO 11600-F&G 25LM.
- Conforms to SNJF (Façade & Vitrage).
- Excellent adhesion to a wide range of substrates without priming.
- UV radiation, weather and ageing resistant.
- Extremely long service life.
- Low odour.
- Non-corrosive.

Application

• For sealing joints, seams and cracks in bathroom, kitchen, toilet, shower, car, boat and caravan. Sealing of expansion joints between porous and non-porous substrates including concrete, masonry, brick, aluminium (lacquered, anodized, painted,...), PVC, glass, ceramics and most plastics. When in doubt, please perform an adhesion test and make use of a primer.

Packaging

- Cartridge 310 ml
- Sausage 400 ml
- Sausage 600 ml

Colour

- White

Safety Recommendations

See safety information sheet

Properties

Specifications

Basis	Neutral oxime silicone
Consistency	Paste
Specific gravity	Approx. 1,0 g/ml
Skin forming time	5 – 10 minutes (at 23°C; 50% R.H.)
Curing rate	Approx. 3 mm/24 hr.
Resistance to flow (ISO 7390)	Approx. 0 mm
Application temperature	Between +5°C to +40 °C
Service temperature	-40°C to +150°C
Shore A hardness (ISO 868)	18

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com