



Product description

Zettex PTFE Oil is a very high quality, universal PTFE-based lubricant that can be used in the most extreme conditions. Zettex PTFE Oil ensures perfect adhesion on almost any surface.

Material

Oil/PTFE

Product Properties

- Ready to use
- Dissolves dirt and rust
- Excellent creeping properties
- Withstands very cold and very hot temperatures
- Lubricates up to 250°C
- Highly adhesive on all surfaces

Applications

For the long-lasting lubrication of all moving or hinged surfaces. For lubricating chains that are exposed to extreme conditions. As lubrication in lathes. As an universal lubrication on rusty surfaces.

Available forms

- Aerosol 500ml

Colour

Transparent/white

Safety recommendations

See safety data sheet

Technical data

Properties	Specification
Change in condition/boiling point	approx. 280°C
Density g/ml (20°C)	0,85gram/cm ³ DIN 51757
Viscosity mPas (20°C)	100cst
pH value undiluted (20°C)	12,5 DIN 19261
pH value (20°C)	11,6
Flash point (°C)	160 DIN 51755
Auto-ignition temperature (°C)	220 DIN 51794
Solubility in water (20°C)	Insoluble

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com