



Product description

Zettex Superlube Hexaflon is spray designed to deposit a dry film, low friction surface, effective over a wide service temperature range. The Superlube is resistant against temperatures between -40 °C and 220 °C .

Product benefits

- Extremely fast drying
- Outstanding chemical resistance.
- Outstanding light resistance
- Exceptional thermal stability
- Non-grease dry film does not attract airborne dirt and grit.
- Lowest coefficient of friction of all lubricants.

Applications

Zettex RVS Spray is suitable for all substrates including wood, metals, rubbers and plastics, and is particularly beneficial in the assembly/disassembly of pre-treated components. Please don't use it on any surface where application of a slippery film may create a health hazard.

Shake can thoroughly before use. Hold upright, and spray from a distance of 15 to 30cm. Take care to avoid overspray, especially on floors.

Packaging

- Aerosol 500 ml.

Colour

- Transparent

Safety recommendations

- Please read our MSDS before using this product.

Technical data

Properties	Specification
Appearance	An opaque, non-homogeneous milky liquid
pH	Not applicable
Specific Gravity	0.700 +/- 0.15 at 20 degrees
Flammability, as supplied	Extremely flammable, flash point below -20
Composition Data	A dispersion of PTFE in isopropanol, and naphtha [petroleum], hydrotreated, light, in a butane/isobutane/propane propellant.
Non Volatiles % m/m	0.1-5.0
Service temperature (Continuous)	Up to 250 °C
Active content % m/m , as supplied	40-50
Consistency	Free flowing liquid
Service temperature (Intermittent)	Up to 300 °C

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com