Welding Spray





Product description

Zettex Welding Spray is an environmental health friendly spray without silicons. Can be sprayed in al directions and is non-flammable.

Product benefits

- Dissolves and emulsifies all conventional automotive oils and greases.
- Ease of use.
- Fast use. Instantaneous emulsification in water

Applications

You can use Zettex Welding Spray on any metallic substrate, for the removal of greases, oils, bitumen and tar stains, waxes etc. This product is also suitable for spot removal use on concretes, and on many plastics and painted surfaces subject to successful assessment on an inconspicuous area. Please don't use it on asphalt surfaces.

Shake the Welding Spray before use. Spray liberally on the designated area. Allow to remain in contact with the surface for a few minutes to penetrate and solublise contaminants, and rinse off with water. Brushing or other forms of agitation will assist in effective solublisation of deposits. Always dispose of contaminated materials in a sealable metal bin to prevent fire risk.

Packaging

• Aerosol 500 ml.

Colour

Transparent

Safety recommendations

• Please read our MSDS before using this product.

Technical data

Properties	Specification
Appearance	A colourless liquid with a hydrocarbon
	odour
рН	Not applicable
Specific Gravity	0.785 +/- 0.015
Flammability, as supplied	Extremely flammable, flash point below -20
Composition Data	A solution of coconut diethanolamide and synthetic fragrance in white spirit and xylene, in a butane/isobutane/propane propellant.
Non Volatiles % m/m	1.00-5.00
Service temperature	Designed for use at ambient
	temperatures
Active content % m/m , as supplied	70-80
Viscosity	Thin free flowing liquid

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com