



Product description

Zettex Eco Seal is a facade impregnating on water base. It leads to a perfect repellent application and it can be applied to both dry and damp surfaces. It can be applied on fresh masonry of at least 14 days old, as well.

Material

Ethanol

Benefits

- Repellent
- Paintable with synthetic paints.
- Application on most common materials.
- Dirt repellent.

Application

The Zettex Eco Seal is ready to use. It can be applied on almost every surface, for example on limestone, bricks, concrete, sandstone and plaster. Zettex Eco Seal is paintable with synthetic paints, it is dirt repellent it decreases lime retirement and frost damage on stone and joint works. It is alkali and acid proof as well.

Packaging

- Barrel 1, 5 and 20 L.

Storage

24 months if stored in unopened, original packaging. Store at temperatures between 5°C and 25°C.

Technical data

Basic raw material	Ethanol
Consumption per M ²	0,5 L
Isocyanate level	0%
Product property 1	Façade Impregnation
Product property 2	Flooring and roofing felt cover
Product property 3	Don't apply when temperature is below 5°C
Product property 4	Ready to use.

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com