



Product description

Zettex Flexcryl Exterior is a high quality sealer which is paintable with almost all types of paint systems and avoids cracking and discoloring. Besides that, the Flexcryl Exterior is suitable for outdoor use. Flexcryl Exterior is suitable for the sealing of joints between window frames of wood and metal. It is also suitable for joints between walls and stairs and for concrete and ceiling elements.

Material

Acryl

Advantages

- Directly paintable with all types of paint.
- Non crack
- For indoor and outdoor use
- Non corrosive
- Adheres to every surface without the use of a primer

Application

Surfaces to be sealed should be clean and dry, free of dust or grease, which could cause a deficient adherence. You can use Zettex Proficleaner to clean the surfaces. Zettex Flexcryl Exterior can be overpainted once it is cured. After using Zettex Flexcryl Exterior, you can clean hands with Zettex Cleaning Wipes.

Packaging

- 310 ml cartridge

Packaging

- Please read our MSDS before using this product



Storage

Zettex Flexcryl Exterior has a shelf life of 12 months, stored in a dry place at or below +25°C in its original container.

Technical Data

| | |
|----------------------------------|------------------------|
| Aspect | Acryl |
| Specific gravity | 1.47 g/cm ³ |
| Skinning time | 12-20 min |
| Application temperature | +5 to +35°C |
| After curing service temperature | -20 to +80°C |
| Hardness Shore A | 17 (ISO 868) |
| Elongation at break | 200 % |

Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com