



### Product description

Zettex Rooftex is a unique repair, mounting and caulking adhesive formulated on the basis of rubber with a glass fibre reinforcement. Can be applied to wet substrates. Can be used over a wide temperature range: (from -12 °C to +50°C.)

### Material

Fiber-reinforced bitumen

### Advantages

- For reparation of cracks, tears and blistering on bituminous roofs and gutters.
- Finishing mastic for sealing seams between roofing sheets around chimneys, drains, domes, elevations and air ducts.
- Adhesion of shingles and insulation (insulation must be solvent-compatible).
- Can also be used as a cold adhesive for installing corrugated roofing sheets, skylights and dome lights.
- Excellent bonding of steel, zinc, lead, copper, tin, wood, stone, concrete, asphalt, pvc and polyester.
- Can be applied on wet surfaces

### Instructions

Apply Zettex Rooftex to surfaces that are free of dirt and grease. Clean tools with Zettex Proficleaner.

### Packaging

- Cartridge 310 ml.

### Safety recommendations

Make sure you have read our MSDS carefully before using this product.

### Storage

Can be stored for a period of up to 12 months, if stored in a dry location and in well-sealed packaging. Keep free from frost.

### Zettex Europe B.V.

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com



**Technical data**

UV stability	Good
Water resistance	Good
Processing temperature	-12 °C to +50°C
Base	Bitumen, rubber, polymers, resin and fibre fortification
Physical state	Viscous paste
Colour	Black
Flash point cc (astm d93)	>55 °C (Pensky Martens)
Viscosity	>60 sec (150 Cup 6 mm, 23 °C)
Density	Ca 1,29 kg/L at 20 °C
Fluidity	Nil
Solid matter	Ca 88 %

**Zettex Europe B.V.**

Blokweg 8 • 4761 RA • Zevenbergen • The Netherlands

T +31 (0)888-93 88 39 • F +31(0)888-93 88 88

I www.zettex.com • E info@zettex.com

